

Article

Assessment of Wind Energy Potential as a Power Generation Source: A Case Study of Eight Selected Locations in Northern Cyprus

Mohamad M. Alayat¹, Youssef Kassem^{1,2,*} and Hüseyin Çamur¹

- 1 Department of Mechanical Engineering, Engineering Faculty, Near East University, 99138 Nicosia (via Mersin 10 Turkey), Cyprus; mohammedalayat85@gmail.com (M.M.A.); huseyin.camur@neu.edu.tr (H.C.)
- 2 Department of Civil Engineering, Civil and Environmental Engineering Faculty, Near East University, 99138 Nicosia (via Mersin 10 Turkey), Cyprus
- * Correspondence: yousseuf.kassem@neu.edu.tr; Tel.: +90-(392)-2236464

Received: 8 September 2018; Accepted: 4 October 2018; Published: 10 October 2018



Abstract: This paper presents a techno-economic assessment of the wind power potential for eight locations distributed over the Northern part of Cyprus. The wind speed data were collected from the meteorological department located in Lefkoşa, Northern Cyprus. Ten distribution models were used to analyze the wind speed characteristics and wind energy potential at the selected locations. The maximum-likelihood method was used for calculating the parameters of the distribution functions. The power law model is utilized to determine the mean wind speed at various heights. In addition, the wind power density for each location was estimated. Furthermore, the performances of different small-scale vertical axis 3-10 kW wind turbines were evaluated to find those that were suitable and efficient for power generation in the studied locations. The results showed that the annual mean wind speed in the regions is greater than 2 m/s at a height of 10 m. Moreover, it is indicated that Generalized Extreme Value distribution provided the best fit to the actual data for the regions of Lefkoşa, Ercan, Girne, Güzelyurt, and Dipkarpaz. However, the Log-Logistic, Weibull, and Gamma distributions gave a better fit to the actual data of Gazimağusa, YeniBoğaziçi, and Salamis, respectively. The Rayleigh distribution does not fit the actual data from all regions. Furthermore, the values of wind power densityat the areas studied ranged from 38.76 W/m² to 134.29 W/m² at a height of 50 m, which indicated that wind energy sources in these selected locations are classified as poor. Meanwhile, based on the wind analysis, small-scale wind turbine use can be suitable for generating electricity in the studied locations. Consequently, an Aeolos-V2 with a rating of 5 kW was found to be capable of producing the annual energy needs of an average household in Northern Cyprus.

Keywords: Northern Cyprus; probability density functions; statistical modeling; wind speed characterization

1. Introduction

Renewable energies such as wind, solar, geothermal and hydro are clean, environmentally friendly, and inexhaustible. Today, wind energy is widely used to produce electricity in many countries. It is becoming the fastest growing renewable energy in the world. Renewable energy conversion systems are popular due to the emerging need for clean energy production throughout the world and wind energy conversion systems (wind turbine) are one of the fastest growing alternatives among these renewable technologies. Before investing in a wind energy harvesting system at a specific location, the available wind energy (potential) and the feasibility of utilizing a wind energy conversion system need to be assessed to use the full potential of the available kinetic energy that wind can provide.



The first parameters that need to be considered are the speed and characteristics of the wind at the given location [1,2].

In this regard, probability density functions (PDFs) and cumulative distribution functions (CDFs) are usually used for describing the wind speed and wind power distribution in many regions around the world and relevant studies can be found in the recent literature [2–6]. Al Zohbi et al. [2] investigated the wind characteristics using actual wind data for five sites in Lebanon. They concluded that wind power had the potential to reduce the electricity crisis in Lebanon. Bilir et al. [3] analyzed the wind speed characteristics in the Incek region of Ankara in Turkey using actual wind data measured at various heights (20 and 30 m). It was found that the wind energy source in this region could be classified as poor and small capacity wind turbines could be used to produce electricity. More recently, Ammari et al. [4] evaluated the wind power for five different locations in Jordan and examined the feasibility of using different wind turbines with various energy rated capacities for the potential to be utilized in wind farms. The results showed that Aqaba Airport and Ras-Muneef have a good wind speed for generating electricity, while the desert locations of Safawi and Azraq South have a moderate wind energy generation potential and Queen Alia Airport has a poor wind energy potential.

The accuracy of these distributions, characterized by their ability to fit the observed data, has a significant impact on the efficiency and uncertainty of the estimated wind energy productions at a particular site. In the literature, some well-known PDFs and CDFs, including Weibull, Rayleigh, Generalized Extreme Value, Gamma, Normal, Log-normal, Logistic, Log-logistic, and Inverse Gaussian [7–12], have been used to model the wind speed and power density distributions. For instance, Ouarda et al. [7] investigated the wind speed characteristics of nine stations in UAE using eleven distribution functions. The maximum likelihood, moments, least-square and L-moments methods were used to calculate the parameters of the distribution functions. The results indicated that 2-parameter Weibull, Kappa distribution, and generalized Gamma distribution generally provided the best fit to the wind speed data at all heights and for all stations. Aries et al. [8] assessed the accuracy of eight probability functions for analyzing the wind speed distribution at four locations in Algeria and four methods were used to calculate the parameters of these functions. They concluded that the Generalized Extreme Value and Gamma distribution are the most appropriate fit to wind speed data at the four sites and the L-moments method is the most accurate for calculating the distribution parameters. Masseran [9] studied the distribution of the wind power density at six stations in Malaysia using Weibull, Gamma, and Inverse Gamma density functions. The maximum likelihood method was used to estimate the parameters of the models. It was found that the Weibull and Gamma PDF was able to provide a good approximation of the observed wind speed data foreach station. Thus, these PDF models were reliable for estimating the wind energy potential in the studied sites.

Electrical energy in Northern Cyprus is produced by fossil fuels and a photovoltaic power plant, which is located in Serhatköy. The power generation in Northern Cyprus is around 212 MW for the diesel generator and 1.27 MW for the photovoltaic power plant, i.e., the total power generation in Northern Cyprus is approximately 300 MW [13–15]. Additionally, population growth and other factors in Northern Cyprus have led to an increase in the demand for fossil fuels. As a result, energy sources such as wind and solar energy can be considered as alternative energy resources for generating electricity. It is important to evaluate the wind potential in Northern Cyprus and select the proper distribution function for analyzing the wind speed characteristics. However, the literature shows that there is a lack of studies that have investigated the wind power potential in Northern Cyprus; therefore, significant attention is required to assess the wind energy resources to provide suitable data for estimating the wind power potential.

Consequently, the primary goal of this study is to determine the best locations with high potential for wind resources at different locations and to provide suitable data for evaluating the potential wind power output from wind power systems. Thus, this paper aims to analyze the wind speed characteristics in eight regions, namely, Lefkoşa, Ercan, Girne, Güzelyurt, Gazimağusa, Dipkarpaz, Yeni Boğaziçi and Salamis in Northern Cyprus. The data consists of monthly data, annual data, and

wind speed direction data. In particular, the analysis of wind speeds for each region was conducted for various periods. Thus, the wind speed data were collected from the Meteorology Department located in Lefkoşa. Ten distribution functions were applied to explore the wind speed characteristics and to determine the wind power potential in each region. The wind power density as a function of hub height is studied in order to classify the wind energy resources in Northern Cyprus. Moreover, a technical and economic assessment has been made for the generation of electricity using vertical axis wind turbines at eight locations. The reasons for choosing a vertical axis wind turbine instead of a horizontal axis wind turbine are: (a) they are good for a low-wind-speed environment; (b) they can be installed in locations with restricted space such as rooftops, buildings or on top of communication towers; and (c) there is no need for a yaw mechanism since they operate independently from the wind direction.

The rest of the paper is structured as follows: Section 2 presents the overall information about the collected wind data, wind data adjustment, and analysis procedure. Section 3 describes the wind speed characteristics at the studied locations and analyzes the wind power densities at different heights to evaluate the wind energy potential in detail. It also discusses the economic evaluation and the performance of small-scale vertical axis wind turbines. Section 4 presents the discussions, and Section 4 provides significant conclusions.

2. Materials and Methods

This section presents the statistical analysis of the wind data measured at a height of 10 m at eight locations in Northern Cyprus. Ten distribution functions are used to determine and evaluate the accuracy of the distribution that best fits the wind speeds of the location. The power law model is utilized to determine the wind speeds at different heights. A technical and economic assessment has been made for the generation of electricity using wind turbines at the studied locations. A flow chart given in Figure 1 is to illustrate the analysis procedure of this study.



Figure 1. The flowchart of the analysis procedure of the present study.

2.1. Measurement Data

The wind measurement data that were collected from the Meteorological Department in Lefkoşa, Northern Cyprus, have been analyzed. The data were measured every 1 h by an anemometer at a height of 10 m. The data used for this work are monthly data using a simple statistical method to calculate the average monthly wind speed. The coordinates, records period and characteristics of the selected locations are presented in Table 1. In addition, the detailed geographic information of the selected meteorological stations is illustrated in Figure 2.

Location	Coord	linates	Period Records	Year	Characteristics of the Location		
Locution	Latitude (°N)	Longitude (°E)	i chidu Accolub	icui	churacteristics of the Location		
Lefkoşa	35°11′8.0376″	33°22′56.1936″	2008-2016	9	Surrounded by building		
Ercan	35°9′31.5828″	33°30′14.364″	2000-2016	17	Airport		
Girne	35°19′26.328″	33°18′50.274″	2000-2016	17	Coastal		
Güzelyurt	35°12′44.3412″	32°58′39.2412″	2000-2016	17	Coastal		
Gazimağusa	35°6′53.6832″	33°55′9.282″	2000-2016	17	Coastal		
Dipkarpaz	35°37′3.6552″	34°24′31.4316″	2005-2016	12	Coastal		
YeniBoğaziçi	35°19′0.3864″	33°57′14.7492″	2011-2016	6	Coastal		
Salamis	35°12′20.5056″	33°53′56.5584″	2009-2016	8	Coastal		

Table 1. The details of each location used in this study.



Figure 2. The geographic location of the study area.

2.2. Probability Distribution Functions

Knowledge of wind speed data is required for renewable resource assessment. Several distribution functions are given in the literature to present the wind speed data in selected regions. In this paper, ten probability distribution functions are used to analyze the distributions of wind speed at the selected regions, as shown in Table 2. Furthermore, in the literature, there are various methods available to compute the parameters of the distribution functions, such as the graphical method, the method of moments, and the maximum likelihood method [16]. In this study, the parameter values for each distribution function were calculated using the Maximum likelihood method. Furthermore, the Easy fit and Matlab R2015a software with a CPU- Intel Xeon E5-16XX, 8 core, 64GB ram, and 64-bit Operating System were used in order to obtain the parameters of the distribution functions.

Γ	listribution	Function]	PDF	CDF			
Weibull (W)			$PDF = \left(\frac{k}{d}\right)$	$\left(\frac{v}{c}\right)\left(\frac{v}{c}\right)^{k-1}exp$	$p\left(-\left(\frac{v}{c}\right)^k\right)$	CDF = 1 - exp(-	$-\left(\frac{v}{c}\right)^k$		
Gamma (G)			$PDF = \frac{v}{\alpha^{\beta}}$	$\frac{v^{\beta-1}}{\Gamma(\beta)}exp\left(-\frac{v}{\beta}\right)$)	$CDF = rac{\gamma\left(eta,rac{ u}{lpha} ight)}{\Gamma(eta)}$			
Lognormal (LN)			$PDF = \frac{1}{v\sigma}$	$\frac{1}{\sqrt{2\pi}}exp\left[-\frac{1}{2}\right]$	$\left(\frac{\ln(v)-\mu}{\sigma}\right)^2$	$CDF = \frac{1}{2} + erf\left[\frac{ln(v)-\mu}{\sigma\sqrt{2}}\right]$			
Logistic (L)			$PDF = \frac{exp\left(-\frac{v-\mu}{\sigma}\right)}{\sigma\left\{1 + exp\left(-\frac{v-\mu}{\sigma}\right)\right\}^{2}}$			$CDF = \frac{1}{1 + exp\left(-\frac{v-\mu}{\sigma}\right)}$			
Log-Logistic (LL)			$PDF = \left(\cdot \right)$	$\frac{\left(\frac{\beta}{\alpha}\left(\frac{v}{\alpha}\right)^{\beta-1}\right)}{\left(1+\frac{v}{\alpha}\right)^{\beta}}\right)^{2}$	2	$CDF = \frac{1}{\left(1 + \frac{v}{\alpha}\right)^{-\beta}}$			
Inverse Gaussiar	ı (IG)		$PDF = \left(\frac{1}{2}\right)$	$\left(\frac{\lambda}{2\pi v^2}\right)^{\frac{1}{2}}e^{\left(\frac{-\lambda(v-2\mu^2)}{2\mu^2}\right)^{\frac{1}{2}}}$	$\left(\frac{\mu}{v}\right)^2$]	$CDF = \Phi\left(\sqrt{rac{\lambda}{\overline{v}}}\left(rac{v}{\mu}-1 ight) ight)$	$+ exp\left(\frac{2\lambda}{\mu}\right)$	$\Phi\left(-\sqrt{rac{\lambda}{\overline{v}}}\left(rac{v}{\mu}+1 ight) ight)$	
Generalized Extreme Value (GEV)			$PDF = \frac{1}{\alpha} \left[1 - \frac{\zeta(v) - \mu}{\alpha} \right]^{\frac{1}{\zeta} - 1} exp \left[-\left(1 - 1 - \frac{\zeta(v) - \mu}{\alpha} \right)^{\frac{1}{\zeta}} \right]$			$CDF = exp\left[-\left(1\right)\right]$	$-1-\frac{\zeta(v)-\alpha}{\alpha}$	$\left[\frac{\mu}{\xi}\right]^{\frac{1}{\xi}}$	
Nakagami (Na)			$PDF = \frac{2m^m}{\Gamma(m)\Omega^m} v^{2m-1} e^{\left(-\frac{m}{\Omega}G^2\right)}$			$CDF = \frac{\gamma(m, \frac{m}{\Omega}v^2)}{\Gamma(m)}$			
Normal (N)			$PDF = \frac{1}{\sqrt{2}}$	$\frac{1}{2\pi\sigma^2}exp\left(-\frac{v}{2}\right)$	$\left(\frac{-\mu}{\sigma^2}\right)$	$CDF = \frac{1}{2} \Big[1 + erf \Big]$	$\left(\frac{v-\mu}{\sigma\sqrt{2}}\right)$		
Rayleigh (R)			$PDF = \frac{2v}{c^2}$	$e^{-\left(\frac{v}{c}\right)^2}$		CDF = 1 - exp[-	$-\left(\frac{v}{c}\right)^2$		
τω/	k	Shape parameter	TT	β	Shape parameter	Na	т	Shape parameter	
vv	c, m/s	Scale parameter		α	Scale parameter	_ 1 \u	Ω	Scale parameter	
G	β	Shape parameter	IC	λ	Shape parameter	N	σ	Standard deviation	
0	α	Scale parameter	- 10	μ	Mean parameter	_ 1	μ	Mean parameter	
IN	σ	Shape parameter		μ	Location Parameter	R	c, m/s	Scale parameter	
	μ	Scale parameter	GEV	ζ	Scale parameter				
L.	μ	Location Parameter		α	Shape parameter				
~	σ	Scale Parameter							

Table 2. The expressions of the statistical distributions used in this study [12,14–16].

2.3. Wind Power Density

The wind power density (WPD) value can be regarded as a representative value for the wind energy potential of a region. The model of wind power density describes the distributions of wind energy at various wind speed values. The WPD value in W/m^2 depends only on the air density and the wind speed as given by [17]

$$WPD = \frac{P}{A} = \frac{1}{2}\rho v^3 \tag{1}$$

where *P* is the wind power in W, *A* is a swept area in m², ρ is the air density ($\rho = 1.225$ kg/m³) and *v* is wind speed in m/s.

Moreover, for a period measurement, the mean wind power density (\overline{WPD}) in W/m² can be calculated using Equation (2) [18].

$$\overline{\text{WPD}} = \frac{P}{A} = \frac{1}{2}\rho\overline{v}^3 \tag{2}$$

where \overline{P} is the mean wind power in W and \overline{v} is the mean wind speed in m/s.

If the distribution of wind speed is taken into account, then Equation (1) can be written as [17]

$$\frac{P}{A} = \frac{1}{2}\rho \int_0^\infty v^3 f(v) dv \tag{3}$$

where f(v) is the probability density function (PDF).

Furthermore, the wind power density distribution for a specified distribution function f(v) can be computed as [19]

$$\frac{P}{A} = \frac{1}{2}\rho v^3 f(v) \tag{4}$$

For wind energy assessments, the simple power law model is usually adopted to convert the wind speeds to various heights. It is expressed as [18]

$$\frac{v}{v_{10}} = \left(\frac{z}{z_{10}}\right)^{\alpha} \tag{5}$$

where v is the wind speed at the wind turbine hub height z, v_{10} is the wind speed at the original height z_{10} , and α is the surface roughness coefficient, which depends on the characteristics of the region [13]. In this study, the wind speed data was measured at the height of 10 m above the ground level; therefore, the value of α can be obtained from the following expression [12,18]

$$\alpha = \frac{0.37 - 0.088 ln(v_{10})}{1 - 0.088 ln(z_{10}/10)} \tag{6}$$

2.4. Output Energy of Wind Turbines

The total power output (E_{wt}) of the wind turbine can be expressed by Equation (7) [17,20]. In addition, the power curve of the wind turbines can be approximated with a parabolic law, as given by [21] (Equation (8)).

$$E_{wt} = \sum_{i=1}^{n} P_{wt(i)}t \tag{7}$$

where E_{wt} is total power output and t is the number of hours in the period under consideration.

$$P_{wt(i)} = \begin{cases} P_r \frac{v_i^2 - v_{ci}^2}{v_r^2 - v_{ci}^2} (v_{ci} \le v_i \le v_r) \\ \frac{1}{2} \rho A C_p v_r^2 (v_r \le v_i \le v_{co}) \\ 0 (v_i \le v_{ci} \text{ and } v_i \ge v_{co}) \end{cases}$$
(8)

where v_i is the vector of the possible wind speed at a given site, $P_{wt(i)}$ is the vector of the corresponding wind turbine output power in W, P_r is the rated power of the turbinein W, v_{ci} is the cut-in wind speed (m/s), v_r is the rated wind speed (m/s), and v_{co} is the cut-out wind speed (m/s) of the wind turbine. C_p is the coefficient of performance of the turbine, and it is a function of the tip speed ratio and the pitch angle. The coefficient of performance is considered to be constant for the entire range of wind speed [22] and can be calculated as

$$C_p = 2\frac{P_r}{\rho A v_r^3} \tag{9}$$

The capacity factor (CF) of a wind turbine is the fraction of the total energy generated by the wind turbine over a period to its potential output if it had operated at a rated capacity during the entire time. The capacity factor of a wind turbine based on the local wind regime of a given site can be estimated as [17]:

$$CF = \frac{E_{wt}}{P_r \cdot t} \tag{10}$$

Several methods have been used to estimate the wind energy cost such as PVC methods [23]. The present value of costs (PVC) is given in Reference [23] as the following equation:

$$PVC = \left[I + C_{omr}\left(\frac{1+i}{r-i}\right) \times \left[1 - \left(\frac{1+i}{1+r}\right)^n\right] - S\left(\frac{1+i}{1+r}\right)^n\right]$$
(11)

where r is the discount rate, *i* is the inflation rate, *n* is the machine life as designed by the manufacturer, C_{omr} is the cost of operation and maintenance, *I* is the investment summation of the turbine price and other initial costs, including provisions for civil work, land, infrastructure, installation, and grid integration and *S* is the scrap value of the turbine price and civil work.

The cost per kWh of electricity generated (UCE) can be determined by the following expression [23]:

$$UCE = \frac{PVC}{t \times P_r \times CF}$$
(12)

3. Results

3.1. Description of Wind Speed Data

Table 3 presents the descriptive statistics of each location including the mean velocity, standard deviation, variance coefficient, minimum velocity, median velocity, maximum velocity, Skewness, and Kurtosis. For all locations at a height of 10 m, the mean wind speeds vary from 2.507 m/s to 4.061 m/s. The mean speed and standard deviation values suggest that there is good consistency in the wind behavior. The coefficients of variation are moderately high, ranging from 7.08 to 16.97. During the investigation period, the Skewness value is negative in Lefkoşa, Güzelyurt, and Ercan, which indicates that all distributions are left-skewed. However, the Skewness values of Girne, Gazimağusa, Dipkarpaz, Yeni Boğaziçi, and Salamis are positive, meaning that all distributions are right-skewed. The annual descriptive statistics of wind speed series at the studied locations over various periods to experience different climatic environments are displayed in Table S1 as Supplementary Material.

Location	Mean (m/s)	Standard Deviation	Variation Coefficient	Minimum (m/s)	Median (m/s)	Maximum (m/s)	Skewness	Kurtosis
Lefkoşa	2.513	0.426	16.97	1.882	2.567	3.203	-0.08	-1.01
Güzelyurt	2.561	0.241	9.39	2.119	2.647	2.869	-0.63	-0.61
Girne	2.507	0.264	10.52	2.151	2.451	2.95	0.39	-1.1
Gazimağusa	3.711	0.314	8.47	3.405	3.511	4.142	0.54	-1.8
Ercan	3.567	0.253	7.08	3.238	3.647	3.981	-0.02	-1.36
Dipkarpaz	4.061	0.47	11.58	3.438	4.052	5.006	0.57	-0.22
Yeni-Boğaziçi	3.448	0.338	9.8	3.048	3.403	4.255	1.35	2.15
Salamis	2.965	0.353	11.92	2.606	2.788	3.498	0.52	-1.55

Table 3. The annual descriptive statistics of wind speed series at the eight-selected locations during the investigation period.

3.2. Wind Speed Characteristics at a 10m Height

The mean monthly wind speeds for the eight locations are plotted in Figure 3. As can be seen, the mean monthly wind speeds ranged between 1.88 and 5.01 m/s. The minimum and maximum wind speeds occurred in December inLefkoşa and in March in Dipkarpaz, respectively. Dipkarpaz has the maximum mean annual wind speed of 4.06 m/s, followed by Gazimağusa, Ercan, YeniBoğaziçi, and Salamis, as shown in Figure 4. Moreover, it is observed that the mean annual wind speed values in Lefkoşa, Güzelyurt, and Girne are approximately the same, which is about 2.51 m/s.



Figure 3. The mean monthly wind speed at the eight selected locations during the studied periods.



Figure 4. The mean annual wind speed at the eight selected locations during the studied periods.

3.3. Windrose

The wind direction was recorded for each selected location during the investigation periods. A total of 16 directions were considered, and the wind frequencies for these directions are presented in Figure 5. It is observed that the dominant direction of the wind for Lefkoşa and Güzelyurt was found to be west (W) with frequency values of 15.3% and 19.2%, respectively. Additionally, it can be seen that the wind direction with the most significant frequency was west-northwest (WNW) for Girne, Ercan, and Dipkarpaz. For Gazimağusae, the wind direction with the highest rate is south-southwest (SSW). Moreover, the dominant direction of the wind for YeniBoğaziçi and Salamis was found to be north-northwest (NNW) with frequency values of 9.4% and 9.9%, respectively



Figure 5. The windrose diagram during the studied periods; (**a**) Lefkoşa, (**b**) Güzelyurt, (**c**) Girne, (**d**) Gazimağusa, (**e**) Ercan, (**f**) Dipkarpaz, (**g**) YeniBoğaziçi, and (**h**) Salamis.

3.4. Distribution Function Parameters and Wind Power Density at a 10 m Height

The parameters of ten distribution functions were estimated using monthly wind speed data with the maximum likelihood method. The best distribution among the ten distribution functions for each location was evaluated based on the results of the Kolmogorov–Smirnov tests.

The calculated parameters of each distribution function are presented in Table 4 for each selected location along with their mean velocities. Additionally, Figure 6 shows the fitted PDF and CDF models for the observed wind speed data for each location. Furthermore, Table 5 presents the goodness-of-fit statistics in terms of the Kolmogorov–Smirnov tests for each distribution function. Moreover, a distribution with the lowest Kolmogorov–Smirnov value will be selected to be the best model for the wind speed distribution in the studied location [12].



Figure 6. Cont.



Figure 6. Fitting the probability density function (PDF) and cumulative distribution function (CDF) models to the wind speed data at a height of 10 m (**a**) Lefkoşa, (**b**) Güzelyurt, (**c**) Girne, (**d**) Gazimağusa, (**e**) Ercan, (**f**) Dipkarpaz, (**g**) YeniBoğaziçi, and (**h**) Salamis.

Table 6 presents the ranking of the distribution models for the eight studied locations based on the Kolmogorov–Smirnov tests. Hence, based on the Kolmogorov–Smirnov tests, GEV has the lowest value, which is considered as the best distribution function to study the wind speed characteristics of Lefkoşa, Güzelyurt, Girne, Ercan, and Dipkarpaz and is ranked the overall third best for Gazimağusa and YeniBoğaziçi, while GEV is ranked the fifth best overall for Salamis, as shown in Table 6. Additionally, LL, W, and G are the best distribution for analyzing the wind speeds of Gazimağusa, YeniBoğaziçi, and Salamis, respectively, as shown in Tables 5 and 6. Moreover, it is observed that the Rayleigh distribution function cannot be used to investigate the wind potential in the studied Location, as shown in Table 6.

Distribution	Actual Mean	Lefkoşa	Güzelyurt	Girne	Gazimağusa	Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Functions	Actual Wicali –	2.513	2.561	2.507	3.711	3.567	4.061	3.448	2.965
	Mean	2.513	2.56	2.507	3.711	3.567	4.063	3.447	2.967
C	Variance	0.17	0.061	0.063	0.089	0.059	0.197	0.098	0.121
G	β	37.084	108.258	99.632	155.376	216.209	83.567	121.189	72.68
	α	0.068	0.024	0.025	0.024	0.016	0.049	0.028	0.041
	Mean	2.512	2.578	2.503	4.811	3.566	4.059	3.448	Inf
	Variance	0.161	0.096	0.064	Inf	0.057	0.208	0.117	Inf
GEV	ζ	-0.417	-1.061	-0.068	0.913	-0.401	-0.039	0.12	1.23
	α	0.425	0.301	0.215	0.12	0.251	0.373	0.222	0.117
	μ	2.396	2.586	2.393	3.491	3.495	3.857	3.29	2.686
	Mean	2.513	2.56	2.507	3.711	3.567	4.063	3.447	2.967
IC	Variance	0.176	0.062	0.063	0.088	0.059	0.197	0.096	0.12
IG	μ	2.513	2.56	2.507	3.711	3.567	4.063	3.447	2.967
	λ	90.059	269.797	250.013	580.898	767.167	340.758	427.296	216.968
	Mean	2.521	2.582	2.493	3.683	3.572	4.035	3.405	2.937
т	Variance	0.199	0.067	0.077	0.116	0.073	0.229	0.094	0.159
L	μ	2.521	2.582	2.493	3.683	3.572	4.035	3.405	2.937
	σ	0.246	0.143	0.153	0.187	0.149	0.264	0.169	0.22
	Mean	2.541	2.589	2.5	3.688	3.576	4.05	3.413	2.945
TT	Variance	0.221	0.073	0.077	0.112	0.075	0.229	0.09	0.155
LL	β	0.916	0.946	0.91	1.301	1.271	1.392	1.224	1.071
	α	0.1	0.057	0.061	0.05	0.042	0.065	0.048	0.073
	Mean	2.517	2.561	2.508	3.712	3.567	4.064	3.448	2.968
IN	Variance	0.194	0.068	0.069	0.096	0.065	0.215	0.105	0.132
LIN	σ	0.908	0.935	0.914	1.308	1.269	1.396	1.233	1.081
	μ	0.173	0.102	0.104	0.083	0.071	0.114	0.094	0.122

Table 4. The parameter values of the different distribution functions over the investigated period at a 10 m height.

Distribution	Actual Mean	Lefkoşa	Güzelyurt	Girne	Gazimağusa	Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Functions		2.513	2.561	2.507	3.711	3.567	4.061	3.448	2.965
	Mean	2.513	2.561	2.507	3.711	3.567	4.061	3.448	2.965
NT.	Variance	0.168	0.059	0.063	0.089	0.059	0.199	0.101	0.123
INa	m	9.539	27.97	25.062	38.65	54.48	20.804	29.486	18.059
Ω	Ω	6.48	6.616	6.348	13.863	12.781	16.693	11.992	8.915
	Mean	2.513	2.56	2.507	3.711	3.567	4.063	3.447	2.967
N	Variance	0.18	0.063	0.07	0.099	0.064	0.221	0.114	0.136
IN	μ	2.513	2.56	2.507	3.711	3.567	4.063	3.447	2.967
	σ	0.425	0.252	0.264	0.314	0.253	0.47	0.337	0.369
	Mean	2.256	2.279	2.233	3.299	3.168	3.622	3.068	2.648
R	Variance	1.391	1.419	1.362	2.975	2.743	3.585	2.572	1.915
	с	1.8	1.818	1.782	2.633	2.528	2.89	2.448	2.113
	Mean	2.515	2.565	2.502	3.706	3.565	4.047	3.423	2.963
TA 7	Variance	0.174	0.053	0.082	0.119	0.069	0.279	0.181	0.154
vv	с	2.687	2.665	2.624	3.855	3.68	4.27	3.603	3.129
	k	7.097	13.553	10.537	13.103	16.671	9.169	9.663	9.029

Table 4. Cont.

Inf: Infinity.

Model	Lefkoşa	Güzelyurt	Girne	Gazimağu	isa Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Wibaci				Kolmogoro	v–Smirnov	vStatistic		
G	0.1414	0.2274	0.1532	0.3101	0.1863	0.1290	0.2460	0.2066
GEV	0.1289	0.1395	0.1176	0.2785	0.1714	0.1118	0.2005	0.2556
IG	0.1507	0.2145	0.1673	0.3213	0.1769	0.1440	0.2590	0.2723
L	0.1622	0.2330	0.1772	0.3382	0.1900	0.1535	0.2484	0.2875
LL	0.1892	0.2436	0.1285	0.2414	0.2318	0.1397	0.1979	0.2313
LN	0.1504	0.2337	0.1522	0.3209	0.1938	0.1438	0.2343	0.2627
Na	0.1392	0.2261	0.1565	0.3081	0.1833	0.1267	0.2520	0.2554
Ν	0.1400	0.2166	0.1663	0.3157	0.1777	0.1367	0.2583	0.2670
R	0.3565	0.4160	0.4391	0.4837	0.4764	0.4305	0.4587	0.4548
W	0.1509	0.2094	0.1421	0.2602	0.1921	0.1325	0.1691	0.2360

Table 5. The results of the goodness-of-fit and the selected distribution (in bold) for each location.

Table 6. The ranking of the distribution functions for all locations at a height of 10 m based on the goodness-of-fit statistics.

Statistic	Location	Rank of the Distribution Function									
Statistic	Location	1	2	3	4	5	6	7	8	9	10
	Lefkoşa	GEV	Na	Ν	G	LN	IG	W	L	LL	R
	Güzelyurt	GEV	W	IG	Ν	Na	G	LN	L	LL	R
	Girne	GEV	LL	W	LN	G	Na	Na	IG	L	R
Kalmagaran Smirnan	Gazimağusa	LL	W	GEV	Na	G	Ν	LN	IG	L	R
Kolillogolov–Sillillov	Ercan	GEV	IG	Ν	Na	G	L	W	LN	LL	R
	Dipkarpaz	GEV	Na	G	W	Ν	LL	LN	IG	L	R
	YeniBoğaziçi	W	LL	GEV	LN	G	L	Na	Ν	IG	R
	Salamis	G	LL	W	Na	GEV	LN	Ν	IG	L	R

Table 7 shows the wind power density values that have been estimated based on the mean actual wind speed and density functions for each location. It is found that the mean actual wind power density (W/m^2) is in the range of 9.63 W/m^2 and 40.95 W/m^2 . Dipkarpaz and Gazimağusa have a higher mean wind power density compared with the other locations.

Model	Lefkoşa	Güzelyurt	Girne	Gazimağu	isa Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Actual	9.70	10.27	9.63	31.25	27.75	40.95	25.06	15.94
G	9.71	10.26	9.63	31.25	27.75	41.00	25.04	15.97
GEV	9.70	10.48	9.59	68.09	27.72	40.88	25.06	-
GI	9.71	10.26	9.63	31.25	27.75	41.00	25.04	15.97
L	9.80	10.53	9.47	30.55	27.86	40.18	24.14	15.49
LL	10.04	10.61	9.55	30.67	27.97	40.61	24.31	15.62
LN	9.75	10.28	9.64	31.27	27.76	41.06	25.06	15.99
Na	9.70	10.27	9.63	31.26	27.75	40.96	25.07	15.94
Ν	9.71	10.26	9.63	31.25	27.75	41.00	25.04	15.97
R	7.02	7.24	6.81	21.96	19.45	29.06	17.66	11.35
W	9.73	10.32	9.58	31.12	27.70	40.54	24.52	15.91

Table 7. The mean wind power density (W/m^2) of all selected locations at a height of 10 m.

The surface roughness values of the eight selected locations determined using Equation (6) are presented in Table 8. The annual mean wind speed values of these locations at different heights (30, 50, and 90 m) are calculated using the power law method (Equation (5)) and summarized in Table 8. It is observed that as the height above the ground increases, the wind speed also increases. The best wind speed for installing wind turbines should be in the range of 6.7 and 11 m/s according to Mostafaeipour [24]. Therefore, Dipkarpaz is the best locationfor installing wind turbines with a hub

height greater than 90 m. In addition, it is observed that at a height of 90 m, the annual mean wind speed in Gazimağusa, Ercan, and YeniBoğaziçi is above 6 m/s.

Location	Lefkoşa	Güzelyurt	Girne	Gazimağusa	Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
α	0.290	0.288	0.290	0.255	0.258	0.247	0.261	0.275
Mean (m/s] at 10 m	2.513	2.561	2.507	3.711	3.567	4.061	3.448	2.965
Mean (m/s] at 30 m	3.447	3.510	3.443	4.908	4.735	5.322	4.591	4.005
Mean (m/s] at 50 m	3.994	4.064	3.990	5.589	5.402	6.036	5.246	4.607
Mean (m/s] at 90 m	4.731	4.811	4.728	6.490	6.287	6.976	6.115	5.412

Table 8. The roughness values (α) and mean wind speed at various heights of the studied locations.

The 90 m synthesized data for the studied locations is presented in Figure 7. As per the actual data at 10 m, the synthesized data is also matched by using ten distribution functions. Moreover, Table 9 shows the calculated parameters, mean speed, and wind power density (WPD) of each distribution functions at a height of 90 m. Mean speed and WPD values vary from 4.204 to 7.877 m/s and 45.430 to 298.865 W/m², respectively. The maximum value of the annual wind power of 298.865 W/m² is recorded in Gazimağusa, whereas the minimum value of 45.430 W/m² is obtained in Girne.



Figure 7. Cont.



Figure 7. Fitting PDF and CDF models to the wind speed data at a height of 90 m (**a**) Lefkoşa, (**b**) Güzelyurt, (**c**) Girne, (**d**) Gazimağusa, (**e**) Ercan, (**f**) Dipkarpaz, (**g**) YeniBoğaziçi, and (**h**) Salamis.

Furthermore, Table 10 shows the results of goodness-of-fit and the selected distribution for each location at a height of 90 m. Based on the Kolmogorov–Smirnov tests, GEV function is the highest match for studying the wind speed characteristics at Lefkoşa, Güzelyurt, Girne, Ercan and Dipkarpaz. However, LL, W and G have the best distributions for analyzing the wind speed for Gazimağusa, YeniBoğaziçi and Salamis, respectively.

	Value	Lefkoşa	Güzelyurt	Girne	Gazimağusa	Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Distribution function	Actual mean	4.753	4.818	4.736	6.497	6.292	6.991	6.124	5.425
	ActualWPD	65.669	68.403	64.971	167.721	152.297	208.899	140.425	97.618
	Mean	4.732	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	Variance	0.398	0.14	0.134	0.162	0.118	0.379	0.2	0.262
G	β	56.278	165.493	166.816	260.407	335.768	128.501	187.288	111.84
	α	0.084	0.029	0.028	0.025	0.019	0.054	0.033	0.048
	WPD	64.78	68.086	64.68	167.219	151.874	207.728	139.825	96.915
	Mean	4.731	4.72	4.724	7.877	6.284	6.971	6.116	Inf
	Variance	0.381	0.363	0.131	Inf	0.113	0.39	0.23	Inf
CEV	ζ	-0.437	-1.074	-0.136	0.903	-0.404	-0.062	0.101	1.144
GEV	α	0.658	0.582	0.327	0.173	0.355	0.524	0.321	0.185
	μ	4.559	4.738	4.575	6.191	6.185	6.699	5.895	5.005
	WPD	64.737	64.289	64.48	298.865	151.769	207.18	139.883	-
	Mean	4.732	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	Variance	0.408	0.143	0.134	0.161	0.118	0.377	0.196	0.26
IG	μ	4.732	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	λ	259.944	779.785	790.29	1701.41	2103.12	900.325	1167.69	609.158
	WPD	64.78	68.086	64.68	167.219	151.874	207.728	139.825	96.915
	Mean	4.745	4.846	4.711	6.454	6.293	6.943	6.058	5.369
	Variance	0.467	0.156	0.16	0.207	0.146	0.44	0.191	0.342
L	μ	4.745	4.846	4.711	6.454	6.293	6.943	6.058	5.369
	σ	0.377	0.218	0.22	0.251	0.211	0.366	0.241	0.322
	WPD	65.33	69.578	63.937	164.406	152.403	204.693	135.933	94.616
	Mean	4.77	4.854	4.719	6.46	6.298	6.959	6.067	5.379
	Variance	0.504	0.166	0.159	0.202	0.149	0.439	0.183	0.334
LL	β	1.552	1.576	1.548	1.863	1.838	1.936	1.8	1.677
	α	0.081	0.046	0.046	0.038	0.034	0.052	0.039	0.059
	WPD	66.37	69.93	64.274	164.831	152.771	206.107	136.571	95.16

Table 9. Distribution parameters and wind power density at 90 m.

W

c k

WPD

5.005

8.731

64.823

4.973

16.785

68.433

	Value	Lefkoşa	Güzelyurt	Girne	Gazimağusa	Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Distribution function	Actual mean	4.753	4.818	4.736	6.497	6.292	6.991	6.124	5.425
	ActualWPD	65.669	68.403	64.971	167.721	152.297	208.899	140.425	97.618
	Mean	4.736	4.812	4.73	6.492	6.287	6.98	6.116	5.414
	Variance	0.447	0.156	0.145	0.174	0.129	0.412	0.214	0.284
LN	σ	1.545	1.568	1.551	1.868	1.837	1.939	1.808	1.684
	μ	0.14	0.082	0.08	0.064	0.057	0.092	0.075	0.098
	WPD	64.964	68.154	64.725	167.29	151.937	207.926	139.899	97.018
	Mean	4.731	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	Variance	0.391	0.137	0.135	0.163	0.117	0.382	0.204	0.264
Na	m	14.431	42.258	41.659	64.736	84.281	32.008	45.888	27.847
	Ω	22.778	23.279	22.501	42.295	39.629	49.072	37.603	29.554
	WPD	64.77	68.077	64.685	167.229	151.874	207.76	139.856	96.934
	Mean	4.732	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	Variance	0.424	0.148	0.147	0.178	0.128	0.422	0.229	0.292
Ν	μ	4.732	4.811	4.729	6.491	6.286	6.978	6.115	5.412
	σ	0.651	0.384	0.383	0.422	0.358	0.649	0.478	0.541
	WPD	64.78	68.086	64.68	167.219	151.874	207.728	139.825	96.915
	Mean	4.23	4.276	4.204	5.764	5.579	6.208	5.434	4.818
7	Variance	4.888	4.996	4.829	9.077	8.504	10.531	8.07	6.342
K	с	3.375	3.412	3.354	4.599	4.451	4.953	4.336	3.844
	WPD	46.269	47.807	45.43	117.074	106.182	146.313	98.144	68.385
	Mean	4.733	4.819	4.719	6.481	6.282	6.954	6.077	5.405
	Variance	0.419	0.125	0.183	0.226	0.141	0.548	0.381	0.342

Table 9. Cont.

64.267 Inf: Infinity.

4.904

13.484

6.689

16.804

166.48

6.447

20.73

151.608

7.271

11.375

205.599

6.342

11.96

137.238

5.655

11.189 96.548

Model	Lefkoşa	Güzelyurt	Girne	Gazimağu	isa Ercan	Dipkarpaz	Yeni Boğaziçi	Salamis
Wiouci				Kolmogoro	v–Smirnov	v statistic		
G	0.1416	0.2275	0.1525	0.3104	0.1869	0.1300	0.2446	0.2207
GEV	0.1283	0.1392	0.1177	0.2777	0.1717	0.1120	0.1998	0.3467
IG	0.1446	0.2170	0.1638	0.3194	0.1793	0.1419	0.2550	0.3003
L	0.1584	0.2354	0.1736	0.3375	0.1925	0.1539	0.2440	0.2852
LL	0.1892	0.2436	0.1285	0.2414	0.2318	0.1397	0.1979	0.2313
LN	0.1504	0.2337	0.1522	0.3209	0.1938	0.1438	0.2343	0.2627
Na	0.1403	0.2267	0.1553	0.3089	0.1845	0.1255	0.2499	0.2555
Ν	0.1363	0.2188	0.1631	0.3150	0.1800	0.1325	0.2544	0.2649
R	0.3904	0.4398	0.4591	0.4955	0.4895	0.4520	0.4751	0.4722
W	0.1509	0.2094	0.1421	0.2602	0.1921	0.1325	0.1691	0.2360

Table 10. Results of goodness-of-fit and the selected distribution (in bold) for each location at 90 m.

3.5. Summary of the Eight Selected Locations in Northern Cyprus

In this section, the wind energy potential of the locations is classified according to the average power density values given in Table 11. The wind power densities of the selected locations ranged from 9.7 to 40.88 W/m² at 10 m, 25.07 to 92.07 W/m² at 30 m, and 38.99 to 134.29 W/m² at 50 m. Therefore, the studied locations can be considered to bePower Class 1, which indicates a poor wind energy potential. Commercial wind turbines with high capacities (MWs) are not suitable to be used in all the studied locations. However, the available wind energy potential of the regions can be exploited using small-scale wind turbines.

Lefkoşa Güzelyurt Girne Gazimağusa Ercan Dipkarpaz Yeni Boğaziçi Salamis Variable Value The power density 9.7 10.48 27.72 40.88 9.59 30.67 24.52 15.97 at 10 m (W/m²) The power density 92.07 25.07 26.10 24.89 71.16 64.98 58.12 39.35 at 30 m (W/m²) The power density 38.99 41.28 38.76 105.16 96.49 134.29 86.72 59.88 at 50 m (W/m²) Wind power class 1 (poor) 0.290 0.288 0.29 0.255 0.261 0.275 Surface roughness 0.258 0.247 Mean at 90 m(m/s) 4.73 4.814.73 6.49 6.29 6.98 6.11 5.41

Table 11. The summary of the eight selected locations in Northern Cyprus.

3.6. Economic Analysis of the Wind Turbine

Based on Section 3.5, five commercially available small vertical axis wind turbines (VAWT) were selected, and the required technical specifications are given in Table 12. In this study, the annual output energy and the capacity factor of the wind turbines for the selected locations were calculated using Equations (7) and (10) and summarized in Table 13 for the Aeolos-V2 5 kW rated model and Table S2 as Supplementary Material for other selected wind turbine models. In addition, the effect of hub height on the annual energy and capacity factor from the chosen wind turbine is shown in Table 13 for the Aeolos-V2 5 kW rated model, while Table S2 as Supplementary Material shows the effect of hub heights on the annual energy and capacity factor of other models. It is observed that the Aeolos-V2 the 5 kW rated model was found to be most efficient with a maximum annual energy and capacity factor corresponding to various hub heights for the Lefkoşa, Güzelyurt, Girne, YeniBoğaziçi, and Salamis locations. For other locations, WS-12/8 kW has the lower capacity factor corresponding to hub heights of 20 and 30 m in comparison to the other chosen wind turbines. Furthermore, Table 13 shows the energy unit cost per kWh based on the PVC method. This cost is computed using Equations (11) and (12). It is observed that the Aeolos-V2 5 kW rated model locations.

Model	Rated Power (kW)	Rated Wind Speed (m/s)	Cut-in Wind Speed (m/s)	Rotor Diameter (m)	Rotor Height (m)
WRE.030/3 kW	3	14	2	3.3	2.2
Aeolos-V2 5 kW	5	10	2.5	4.2	5.3
WRE.060/6 kW	6	14	2	3.3	4.4
WS-12/8 kW	8	20	2	2	6
Aeolos-V 10 kW	10	12	2.5	4.2	5.3

Table 12. The vertical axis small wind turbine specifications.

Table 13. The electricity production and financial indices at he eight locations for the Aeolos-V2 5 kW model at various hub heights.

Location	Hub Height (m)	Total Energy Power of Wind Turbine (kW)	CF (%)	UCE (\$/kW)
Lefkoşa	20	43.18	35.98	0.61
	30	75.83	63.19	0.35
	40	104.13	86.77	0.25
Güzelyurt	20	52.44	43.7	0.51
	30	93.91	78.26	0.28
	40	129.85	108.21	0.20
Girne	20	53.63	44.69	0.49
	30	95.42	79.52	0.28
	40	131.63	100	0.20
Gazimağusa	20	296.23	100	0.09
	u 30	402.34	100	0.07
	40	494.28	100	0.05
Ercan	20	247.46	100	0.11
	30	340.64	100	0.08
	40	421.38	100	0.06
Dipkarpaz	20	308.53	100	0.09
	30	417.9	100	0.06
	40	512.67	100	0.05
Yeni Boğaziçi	20	103.69	86.41	0.26
	30	146.03	100	0.18
	40	182.71	152.26	0.15
Salamis	20	84.22	70.18	0.31
	30	125.63	100	0.21
	40	161.52	100	0.16

4. Discussion

The results show thatthe annual mean wind speeds at all locations in Northern Cyprus are generally higher than 2 m/s at a height of 10 m (Figure 4) and themean monthly wind speed varies within the range of 1.8–5 m/s (Figure 3). Based on Figure 4, the locations (Gazimağusa, Dipkarpaz, YeniBoğaziçi, and Salamis) in the eastern part of Northern Cyprus have higher wind speeds compared to the other locations (Lefkoşa, Girne, and Güzelyurt). In fact, higher wind speeds are mostly seen in the south part of Cyprus and only on the top of the Beşparmak Mountains in the north part of Cyprus [25]. Beşparmak gives its depictive name to the whole mountain range and SelviliTepe in the west with the highest peak of 1024 m are the most renowned and outstanding mountains in North Cyprus. According to Solyali et al. [26], the mean annual wind speed at the Selvili-Tepe location is about 5 m/s at 30 m height. As mentioned previously, there is a lack of studies that have investigated the wind power potential in Northern Cyprus. Therefore, this study is aimed to analyze the wind power potential in different locations in the north part of Cyprus. Thus, the results of the collected data and analysis show that Dipkarpaz has better conditions for developing a wind farm with a wind turbine of 90 m hub height, at which the capacity of the wind turbine is 1 MW or above. The airport

(Ercan) is a relatively inappropriatelocatin to install a wind turbine at because this site has a high value of surface roughness, and the turbine will be dangerous to airplanes. Based on the wind power density classes published by the U.S. Department of Energy, the evaluation of the wind resources available in the eight selected locations (which are class 1 wind power site) indicates its suitability for small-scale wind turbine and for off-grid connections (Table 11). From the perspective of the costs of generating electricity, the Aeolos-V2 5 kW model is the most economical option for generating electricity in Northern Cyprus (Table 13 and Table S2).

5. Conclusions

The wind characteristics and wind power potential in several selected locations in Northern Cyprus were discussed. Wind speeds and power density at different heights were estimated using different distribution functions. It is important to note that this step was implemented after the wind analysis at 10 m and after determining the most accurate distribution function. Therefore, it was found that GEV provided the best fit to the actual wind speed data for the regions of Lefkoşa, Güzelyurt, Girne, Ercan, and Dipkarpaz. However, LL, W, and G had the best distribution for analyzing the wind speed of Gazimağusa, YeniBoğaziçi, and Salamis, respectively. All the considered locations have annual mean wind speeds above 2 m/s, and the wind power densities range between 9.59 W/m² to 40.88 W/m² at a height of 10 m. Among the eight studied locations, it was observed that Dipkarpaz had the highest winds. The wind power analysis shows that Dipkarpaz is the best location for harvesting wind energy. A techno-economic assessment was made for the generation of electricity using a small-scale vertical axis wind turbine in all the studied locations. It is found that Aeolos-V2 model with a power rating of 5 kW has the lowest energy production cost among the considered wind turbine technologies. Finally, the exploitation of renewable energy sources such as wind energy can help Northern Cyprus achieve many of its environmental and energy policy targets.

Supplementary Materials: The following are available online at http://www.mdpi.com/1996-1073/11/10/2697/ s1. Table S1: Annual descriptive statistics of wind speed series at eight-selected Location over various period, Table S2: Annual descriptive statistics of wind speed series at eight-selected Location over various period.

Author Contributions: M.M.A. collected the wind data. Y.K. and H.Ç. analyzed the data and wrote the paper.

Funding: This research received no external funding.

Acknowledgments: The authors would like to thank the Faculty of Engineering especially the Mechanical Engineering Department at Near East University for their support and encouragement.

Conflicts of Interest: The authors declare no conflict of interest.

References

- Rasham, A.M. Analysis of Wind Speed Data and Annual Energy Potential at Three locations in Iraq. *Int. J. Comput. Appl.* 2016, 137, 5–16. [CrossRef]
- 2. Oyedepo, S.; Adaramola, M.; Paul, S. Analysis of Wind Speed Data and Wind Energy Potential in Three Selected Locations in South-East Nigeria. *Wind Resour. Future Energy Secur.* **2015**, 3–28. [CrossRef]
- 3. Mostafaeipour, A.; Jadidi, M.; Mohammadi, K.; Sedaghat, A. An analysis of wind energy potential and economic evaluation in Zahedan, Iran. *Renew. Sustain. Energy Rev.* **2014**, *30*, 641–650. [CrossRef]
- 4. Soulouknga, M.; Doka, S.; Revanna, N.; Djongyang, N.; Kofane, T.C. Analysis of wind speed data and wind energy potential in Faya-Largeau, Chad, using Weibull distribution. *Renew. Energy* **2018**, *121*, 1–8. [CrossRef]
- 5. Benatallah, M.; Chegaar, M. Investigation of Wind Characteristics in the Southern Region of Algeria. *Energy Procedia* **2013**, *36*, 707–713. [CrossRef]
- 6. Gökçek, M.; Bayülken, A.; Bekdemir, Ş. Investigation of wind characteristics and wind energy potential in Kirklareli, Turkey. *Renew. Energy* **2007**, *32*, 1739–1752. [CrossRef]
- Bilir, L.; İmir, M.; Devrim, Y.; Albostan, A. An investigation on wind energy potential and small-scale wind turbine performance at İncek region—Ankara, Turkey. *Energy Convers. Manag.* 2015, 103, 910–923. [CrossRef]
- 8. Ammari, H.D.; Al-Rwashdeh, S.S.; Al-Najideen, M.I. Evaluation of wind energy potential and electricity generation at five locations in Jordan. *Sustain. Cities Soc.* **2015**, *15*, 135–143. [CrossRef]

- 9. Baseer, M.; Meyer, J.; Alam, M.M.; Rehman, S. Wind speed and power characteristics for Jubail industrial city, Saudi Arabia. *Renew. Sustain. Energy Rev.* 2015, 52, 1193–1204. [CrossRef]
- 10. Al Zohbi, G.; Hendrick, P.; Bouillard, P. Wind characteristics and wind energy potential analysis in five sites in Lebanon. *Int. J. Hydrog. Energy* **2015**, *40*, 15311–15319. [CrossRef]
- 11. Dabbaghiyan, A.; Fazelpour, F.; Abnavi, M.D.; Rosen, M.A. Evaluation of wind energy potential in province of Bushehr, Iran. *Renew. Sustain. Energy Rev.* **2016**, *55*, 455–466. [CrossRef]
- 12. Masseran, N. Evaluating wind power density models and their statistical properties. *Energy* **2015**, *84*, 533–541. [CrossRef]
- 13. Ozay, C.; Celiktas, M.S. Statistical analysis of wind speed using two-parameter Weibull distribution in Alaçatı region. *Energy Convers. Manag.* **2016**, *121*, 49–54. [CrossRef]
- 14. Ouarda, T.; Charron, C.; Shin, J.; Marpu, P.; Al-Mandoos, A.; Al-Tamimi, M.; Hosary, T.A. Probability distributions of wind speed in the UAE. *Energy Convers. Manag.* **2015**, *93*, 414–434. [CrossRef]
- 15. Aries, N.; Boudia, S.M.; Ounis, H. Deep assessment of wind speed distribution models: A case study of four sites in Algeria. *Energy Convers. Manag.* **2018**, *155*, 78–90. [CrossRef]
- 16. Allouhi, A.; Zamzoum, O.; Islam, M.; Saidur, R.; Kousksou, T.; Jamil, A.; Derouich, A. Evaluation of wind energy potential in Morocco's coastal regions. *Renew. Sustain. Energy Rev.* **2017**, *72*, 311–324. [CrossRef]
- 17. Ayodele, T.R.; Jimoh, A.A.; Munda, J.L.; Agee, J.T. Viability and economic analysis of wind energy resource for power generation in Johannesburg, South Africa. *Int. J. Sustain. Energy* **2013**, *33*, 284–303. [CrossRef]
- Irwanto, M.; Gomesh, N.; Mamat, M.; Yusoff, Y. Assessment of wind power generation potential in Perlis, Malaysia. *Renew. Sustain. Energy Rev.* 2014, *38*, 296–308. [CrossRef]
- Mohammadi, K.; Alavi, O.; Mcgowan, J.G. Use of Birnbaum-Saunders distribution for estimating wind speed and wind power probability distributions: A review. *Energy Convers. Manag.* 2017, 143, 109–122. [CrossRef]
- 20. Gökçek, M.; Genç, M.S. Evaluation of electricity generation and energy cost of wind energy conversion systems (WECSs) in Central Turkey. *Appl. Energy* **2009**, *86*, 2731–2739. [CrossRef]
- 21. Pallabazzer, R. Parametric analysis of wind siting efficiency. J. Wind Eng. Ind. Aerodyn. 2003, 91, 1329–1352. [CrossRef]
- 22. Nouni, M.; Mullick, S.; Kandpal, T. Techno-economics of small wind electric generator projects for decentralized power supply in India. *Energy Policy* **2007**, *35*, 2491–2506. [CrossRef]
- 23. Adaramola, M.; Paul, S.; Oyedepo, S. Assessment of electricity generation and energy cost of wind energy conversion systems in north-central Nigeria. *Energy Convers. Manag.* **2011**, *52*, 3363–3368. [CrossRef]
- 24. Mostafaeipour, A. Feasibility study of harnessing wind energy for turbine installation in province of Yazd in Iran. *Renew. Sustain. Energy Rev.* **2010**, *14*, 93–111. [CrossRef]
- 25. Maxoulis, C.N.; Kalogirou, S.A. Cyprus energy policy: The road to the 2006 world renewable energy congress trophy. *Renew. Energy* **2008**, *33*, 355–365. [CrossRef]
- 26. Solyali, D.; Altunç, M.; Tolun, S.; Aslan, Z. Wind resource assessment of Northern Cyprus. *Renew. Sustain. Energy Rev.* **2016**, *55*, 180–187. [CrossRef]



© 2018 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (http://creativecommons.org/licenses/by/4.0/).